



NOTES:

- ① UNLESS OTHERWISE SPECIFIED, RESISTANCE VALUES ARE IN OHMS, CAPACITANCE VALUES ARE IN MICROFARADS, AND INDUCTANCE VALUES ARE IN MICROHENRYS.
- ② PARTIAL REFERENCE DESIGNATIONS ARE SHOWN; FOR COMPLETE DESIGNATION, PREFIX WITH UNIT AND/OR ASSEMBLY DESIGNATION.
- ③ ON A9U1, PIN 8 IS +VCC, PIN 1 IS GND.
- ④ F1 IS 8A FOR 115 V AC. 4A FOR 230 V AC.
- ⑤ JUMPER PRESENT ON MATING CONNECTOR ONLY WHEN USING DC POWER.
- ⑥ SHOWN STRAPPED FOR 115 V AC. FOR INPUT VOLTAGES LISTED, STRAP TB1 AS FOLLOWS:

	105	115	125	210	220	230	240	250
BLACK	7	7	7	6	6	5	5	4
YELLOW	3	2	1	3	2	2	1	1
RED	6	5	4	3	2	2	1	1

- ⑦ Q1, U2, U3 ARE MOUNTED TO CHASSIS.
- ⑧ Q4, Q5, Q6 ARE TYPE MJ4031
- ⑨ S1 IS MOUNTED ON FRONT PANEL.
- ⑩ TEST POINT VOLTAGES AND WAVEFORMS SHOWN ARE NOMINAL.

