

The Data Book Project

DatasheetArchive.com has launched an ambitious effort to digitize thousands of obsolete data books and technical manuals, making them searchable via the DatasheetArchive website.

Scroll down to see the scanned document.

SMALL-SIGNAL AMPLIFIERS (PRO-ELECTRON SERIES)

Type No.	POLARITY	P _D T _A = 25°C (mW)	V _(BR) CBO Volts	V _(BR) CEO Volts	V _(BR) EBO Volts	DC CURRENT GAIN (h _{FE})				V _{CE(SAT)}		f _T Min. (MHz)	C _{cb} Max. (pF)	N.F. Max. (dB)		
						Conditions		Limits		I _c (mA)	V _{CE} Volts				I _c (mA)	Max. Volts
						I _c (mA)	V _{CE} Volts	Min.	Max.							
BC182A	NPN	300	60	50	6	2	5	120	220	100	0.60	150	5	10		
BC182B	NPN	300	60	50	6	2	5	180	460	100	0.60	150	5	10		
BC212A	PNP	300	60	50	5	2	5	120	220	100	0.60	200	6	10		
BC212B	PNP	300	60	50	5	2	5	180	460	100	0.60	200	6	10		
BC237A	NPN	300	50	45	6	2	5	120	220	10	0.20	150	4.5	10		
BC237B	NPN	300	50	45	6	2	5	180	460	10	0.20	150	4.5	10		
BC238A	NPN	300	30	20	5	2	5	120	220	10	0.20	150	4.5	10		
BC238B	NPN	300	30	20	5	2	5	180	460	10	0.20	150	4.5	10		
BC238C	NPN	300	30	20	5	2	5	380	800	10	0.20	150	4.5	10		
BC239B	NPN	300	30	20	5	2	5	180	460	10	0.20	150	4.5	4		
BC239C	NPN	300	30	20	5	2	5	380	800	10	0.20	150	4.5	4		
BC307A	PNP	300	45	45	5	2	5	120	220	10	0.20	150	6	10		
BC307B	PNP	300	45	45	5	2	5	180	460	10	0.20	150	6	10		
BC308A	PNP	300	25	25	5	2	5	120	220	10	0.20	150	6	10		
BC308B	PNP	300	25	25	5	2	5	180	460	10	0.20	150	6	10		
BC308C	PNP	300	25	25	5	2	5	380	800	10	0.20	150	6	10		
BC309B	PNP	300	20	20	5	2	5	180	460	10	0.20	150	6	4		
BC309C	PNP	300	20	20	5	2	5	380	800	10	0.20	150	6	4		
BC413B	NPN	300	45	30	5	2	5	180	460	10	0.6	250	2.5	2.5		
BC413C	NPN	300	45	30	5	2	5	380	800	10	0.6	250	2.5	2.5		
BC414B	NPN	300	50	45	5	2	5	180	460	10	0.6	250	2.5	2.5		
BC414C	NPN	300	50	45	5	2	5	380	800	10	0.6	250	2.5	2.5		
BC415A	PNP	300	45	35	5	2	5	120	220	10	0.6	200	4.5	2.0		
BC415B	PNP	300	45	35	5	2	5	180	460	10	0.6	200	4.5	2.0		
BC415C	PNP	300	45	35	5	2	5	380	800	10	0.6	200	4.5	2.0		
BC416A	PNP	300	50	45	5	2	5	120	220	10	0.6	200	4.5	2.0		
BC416B	PNP	300	50	45	5	2	5	180	460	10	0.6	200	4.5	2.0		
BC416C	PNP	300	50	45	5	2	5	380	800	10	0.6	200	4.5	2.0		
BC327-16	PNP	300	45	45	5	100	1	100	250	500	0.7	100	12	—		
BC327-25	PNP	300	45	45	5	100	1	160	400	500	0.7	100	12	—		
BC327-40	PNP	300	45	45	5	100	1	250	630	500	0.7	100	12	—		
BC328-16	PNP	300	25	25	5	100	1	100	250	500	0.7	100	12	—		
BC328-25	PNP	625	25	25	5	100	1	160	400	500	0.7	100	12	—		
BC328-40	PNP	625	25	25	5	100	1	250	630	500	0.7	100	12	—		
BC337-16	NPN	625	45	45	5	100	1	100	250	500	0.7	100	12	—		
BC337-25	NPN	625	45	45	5	100	1	160	400	500	0.7	100	12	—		
BC337-40	NPN	625	45	45	5	100	1	250	630	500	0.7	100	12	—		
BC338-16	NPN	625	25	25	5	100	1	100	250	500	0.7	100	12	—		
BC338-25	NPN	625	25	25	5	100	1	160	400	500	0.7	100	12	—		
BC338-40	NPN	625	25	25	5	100	1	250	630	500	0.7	100	12	—		
BC167A	NPN	300	50	45	6	2	5	125	260	10	0.20	150	4.5	10		
BC167B	NPN	300	50	45	6	2	5	240	500	10	0.20	150	4.5	10		
BC168A	NPN	300	30	20	5	2	5	125	260	10	0.20	150	4.5	10		
BC168B	NPN	300	30	20	5	2	5	240	500	10	0.20	150	4.5	10		
BC168C	NPN	300	30	20	5	2	5	450	900	10	0.20	150	4.5	10		
BC169B	NPN	300	30	20	5	2	5	240	500	10	0.20	150	4.5	4		
BC169C	NPN	300	30	20	5	2	5	450	900	10	0.20	150	4.5	5		
BC257A	PNP	300	45	45	5	2	5	125	260	10	0.20	150	6	10		
BC257B	PNP	300	45	45	5	2	5	240	500	10	0.20	150	6	10		
BC258A	PNP	300	25	25	5	2	5	125	260	10	0.20	150	6	10		
BC258B	PNP	300	25	25	5	2	5	240	500	10	0.20	150	6	10		
BC258C	PNP	300	25	25	5	2	5	450	900	10	0.20	150	5	10		
BC259B	PNP	300	20	20	5	2	5	240	500	10	0.20	150	6	4		
BC259C	PNP	300	20	20	5	2	5	450	900	10	0.20	150	6	4		



TO-92
Formed
to
TO-18
(CBE
Pinning)



TO-92
Package
(ECB
Pinning)